

MSB120TO02F

Refrigeration unit Monobloc for ceiling

Autonomous monobloc for positives rooms the small ones and average volumes.

Refrigerating capacity / Coldroom volume **T°ext. +35°C**

T° room +5 °C	1034 W / 5.1 m ³
T° room 0°C	924 W / 4.1 m ³
T° room -5 °C	780 W / 2.9 m ³

Refrigerating capacity / Coldroom volume **T°ext. +40°C**

T° room +5 °C	966 W / 4.4 m ³
T° room 0°C	861 W / 3.4 m ³
T° room -5 °C	720 W / 2.4 m ³

Technical Data

Power nominal absorption	0.6 kW
Voltage	230 V / 1~/ 50 Hz
Intensity nominal absorption	3.5 AMP
Mass	42 KG
Air volume condenser	400 m ³ /h
Air volume évaporator	500 m ³ /h
Air throw	3 m



Monobloc ceiling light fitted with body with integrated electrical equipment box

Compressing hermetic 1/2 cv equipped with integral protection

Expansion of gas by capillaire

Fluid R404A

Cyclic De-icing by automatic gas chaud

Automatic elimination of condensed water,
separated Control panel,

Cable line, micro cable carries, cable light ceiling light and lampe
and for the models BT, cable for resistance carries (L=2,5 m).

OPTIONS:

Condensation by water

Different voltage

Relay of control of the supply voltage