

## **MBX360N01F**

## **Industrial monobloc on the ground for rooms of great volumes.**

Autonomous monobloc fitted with body with built-in electrical equipment box for an industrial application of rooms of great volumes.

### **Refrigerating capacity / Coldroom volume** **T° ext. +35°C**

<b>T°Room +5°C</b>	63480 W / 1798 m <sup>3</sup>
<b>T°Room +0°C</b>	55792 W / 1561 m <sup>3</sup>
<b>T°Room -5°C</b>	48739 W / 1345 m <sup>3</sup>

### **Refrigerating capacity / Coldroom volume** **T° ext. +40°C**

<b>T° Room +5°C</b>	59151 W / 1664 m <sup>3</sup>
<b>T° Room +0°C</b>	51902 W / 1441 m <sup>3</sup>
<b>T° Room -5°C</b>	45379 W / 1245 m <sup>3</sup>



### **Technical Data**

<b>Voltage</b>	400 V / 3N~/ 50 Hz
<b>Power nominal absorption</b>	29.3 kW
<b>Intensity nominal absorption</b>	79.9 AMP
<b>Mass</b>	2075 KG
<b>Air Volume Condenser</b>	34000 m <sup>3</sup>
<b>Air volume evaporateur</b>	31600 m <sup>3</sup>
<b>Air throw</b>	40 m
<b>Defrost Heather</b>	24720 W

Monobloc fitted with body on feet with built-in electrical equipment box,  
Compressor semi hermetic 35 cv equipped with integral protection,  
Ventilators high-output helicoid condensers and low noise level cast solid industrial evaporator on feet/blowing by tube,  
Relaxation of gas by thermostatic pressure reducer,  
De-icing cyclic electric automatic completion,  
Resistant of compressing pre-heating,  
Control of the pressure of condensation with pressure controller,  
Winnow solenoid of line, Indicator of liquid, tank of liquid, Groups charged in R404A,  
Pressostat LP and HP of safety,  
electronic variator speed of the ventilators condensers.

#### **OPTIONS:**

Electronic variator speed of the ventilators condensers,  
Condensation with water,  
Panel of control separate (for one or more machines assembled in same room),  
Monitor of control of the supply voltage,  
different voltage.