

MDB235TD11F

Industrial horizontal Split unit for rooms of means and great volumes.

Autonomous monobloc fitted with body with built-in electrical equipment box for an industrial application of rooms of means and/or great volumes.

Refrigerating capacity / Coldroom volume

T° ext. +35°C

T°Room +5°C	6911 W / 109 m ³
T°Room +0°C	5981 W / 91 m ³
T°Room -5°C	5035 W / 74 m ³

Refrigerating capacity / Coldroom volume

T° ext. +40°C

T° Room +5°C	6418 W / 100 m ³
T° Room +0°C	5554 W / 84 m ³
T° Room -5°C	4657 W / 67 m ³

Technical Data

Voltage	400 V / 3N~/ 50 Hz
Power nominal absorption	3.3 kW
Intensity nominal absorption	8 AMP
Mass	135 KG + 51 KG
Air Volume Condenser	3800 m ³
Air volume évaporateur	4300 m ³
Air throw	11 m
Defrost Heather	4200 W



Group fitted with body envisaged for installation with external with built-in electrical equipment box,
Semi hermetic Compressor 3 cv equipped with integral protection,
Industrial cubic Evaporator with great removable spaces,
Relaxation of gas by thermostatic pressure reducer,
Ventilators high-output helicoid condensers and low noise level,
De-icing cyclic electric automatic completion,
Control of the pressure of condensation,
Winnow solenoid of line,
Indicator of liquid, tank of liquid with preload R404A,
Electromechanical thermostat of regulation integrated in the electrical equipment box.

OPTIONS:

Electronic Variator speed of the rotors condenser,
Condensation with water,
Panel of control separate (for one or more machines assembled in the same room), Relay of control of the supply voltage.