

CDB150N001F**Fast unit of congelation**

especially conceived for the deep freezing of the foodstuffs

Split of refrigeration especially conceived for the congelation of foodstuffs. The units are to be integrated in tunnels of congelation for a final interior temperature about -35°C/-40°C.

Refrigerating capacity / Coldroom volume**T° ext. +35°C**

T° Evaporation -35°C	5215 W
T° Evaporation -40°C	4152 W
T° Evaporation -45°C	3280 W

Refrigerating capacity / Coldroom volume**T° ext. +40°C**

T° Evaporation -35°C	5030 W
T° Evaporation -40°C	4015 W
T° Evaporation -45°C	3175 W

Technical Data

Voltage	400 V /3N~/ 50 Hz
Power nominal absorption	6.9 kW
Intensity nominal absorption	15.5 AMP
Mass	377 KG + 90 KG
Air Volume Condenser	6800 m ³
Air volume evaporateur	7300 m ³
Air throw	26 m
Defrost Heather	8800 W

Fitted with body monobloc planned for installation with external with built-in electrical equipment box,
Semi hermetic Compressor 7,5 cv equipped with integral protection,
Cubic Evaporator,
Relaxation of gas by thermostatic pressure reducers,
Ventilators high-output helicoid condensers and low noise level,
De-icing cyclic electric automatic completion,
Control of the pressure of condensation,
Winnow solenoid of line,
Indicator of liquid, tank of liquid, Group charged in R404A,
Electromechanical thermostat of regulation integrated in the electrical equipment box.

OPTIONS:

Electronic Variator speed of the rotors condenser,
Condensation with water,

Panel of control separate (for one or more machines assembled in the same room), Relay of control of the supply voltage.