

GCU1005U01F- mt

Unit split horizontal super silent room for small volumes with cubic evaporator

Condensing unit or ground support, evaporator cubic ceiling.

Refrigerating capacity / Coldroom volume **T°ext. +35°C**

T° Evaporation -15 °C	722 W
T° Evaporation -10 °C	905 W
T° Evaporation -5 °C	1112 W

Refrigerating capacity / Coldroom volume **T°ext. +40°C**

T° Evaporation -15 °C	649 W
T° Evaporation -10 °C	816 W
T° Evaporation -5 °C	1007 W

Technical Data

Power nominal absorption	0.5/2.82 kW
Voltage	230/1~/50 HZ
Mass	55 KG
Air volume condenser	2000 m³/h
Air volume évaporator	750 m³/h
Air throw	7 M
DB(A)	28
Connections refrigerated aspiration	1/2"
Connections refrigerated liquid	1/4"
Body size	CU1

Features

Group condensation carrossée
cabinet incorporated
hermetic Compressor Pressure
HP security and BP adjustable
tank liquid and liquid line
Soundproofing voice strengthened double skin
 Low
speed ventilation
condenser fan speed changer
Evaporator cubic condenser defrost power
negative regulator valve and accessories
box regulatory Coldface ELIWELL
nitrogen Security Charge

