

HCU1017H01F

Unit split horizontal super silent room for small volumes with cubic evaporator

Condensing unit or ground support, evaporator cubic ceiling.

Refrigerating capacity / Coldroom volume **T°ext. +35°C**

T° Evaporation -25 °C	1487 W
T° Evaporation -30 °C	1153 W
T° Evaporation -35 °C	877 W

Refrigerating capacity / Coldroom volume **T°ext. +40°C**

T° Evaporation -30 °C	1087 W
T° Evaporation -25 °C	1413 W
T° Evaporation -35 °C	824 W

Technical Data

Voltage	230/1~/50 HZ
Power nominal absorption	0.79/4.49 kW
Mass	65 KG
Air volume condenser	2000 m³/h
Air volume évaporator	1500 m³/h
Air throw	7 M
DB(A)	32
Connections refrigerated aspiration	1/2"
Connections refrigerated liquid	1/4"
Body size	CU1

Features

Group condensation carrossée
 cabinet incorporated
 hermetic Compressor Pressure
 HP security and BP adjustable
 tank liquid and liquid line
 Soundproofing voice strengthened double skin
 Low
 speed ventilation
 condenser fan speed changer
 Evaporator cubic condenser defrost power
 negative regulator valve and accessories
 box regulatory Coldface ELIWELL
 nitrogen Security Charge

