

HCU2030B01F

Condensing unit horizontal SUPER SILENT

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -25°C	4110 W
-----------------------------	--------

T° Evaporation -30°C	3296 W
-----------------------------	--------

T° Evaporation -35°C	2555 W
-----------------------------	--------

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -25°C	3659 W
-----------------------------	--------

T° Evaporation -30°C	2918 W
-----------------------------	--------

T° Evaporation -35°C	2241 W
-----------------------------	--------

Technical Data

Voltage	400V/3N~/50 HZ
----------------	----------------

Power nominal absorption	3.11/ 6.34 kW/A
---------------------------------	-----------------

Mass	123 KG
-------------	--------

Air Volume Condenser	3900 M3/H
-----------------------------	-----------

Connections refrigerated aspiration	1 1/8"
--	--------

Connections liquid aspiration	3/8"
--------------------------------------	------

DB(A)	32
--------------	----

Body size	CU2
------------------	-----



STANDARD FEATURES:

Group condensation bodywork cabinet incorporated
semi hermetic compressor BITZER
Elimination vibration and silent aspiration back
Pressure HP security and BP adjustable
soundproofing sound simple or enhanced Low
condenser fan speed 6P
condenser fan speed variator
security nitrogen load.