

## **HCU4075B01F**

## **Condensing unit horizontal SUPER SILENT**

Condensing unit on the ground or support.

### **Refrigerating capacity / Coldroom volume T° ext. +35°C**

|                             |        |
|-----------------------------|--------|
| <b>T° Evaporation -25°C</b> | 9950 W |
| <b>T° Evaporation -30°C</b> | 7940 W |
| <b>T° Evaporation -35°C</b> | 6116 W |

### **Refrigerating capacity / Coldroom volume T° ext. +40°C**

|                             |        |
|-----------------------------|--------|
| <b>T° Evaporation -25°C</b> | 8843 W |
| <b>T° Evaporation -30°C</b> | 7014 W |
| <b>T° Evaporation -35°C</b> | 5349 W |

### **Technical Data**

|                                            |                 |
|--------------------------------------------|-----------------|
| <b>Voltage</b>                             | 400V/3N~/50 HZ  |
| <b>Power nominal absorption</b>            | 5.89/12.04 kW/A |
| <b>Mass</b>                                | 229 KG          |
| <b>Air Volume Condenser</b>                | 7300 M3/H       |
| <b>Connections refrigerated aspiration</b> | 1 3/8"          |
| <b>Connections liquid aspiration</b>       | 1/2"            |
| <b>DB(A)</b>                               | 41              |
| <b>Body size</b>                           | CU4             |



#### **STANDARD FEATURES:**

Group condensation bodywork cabinet incorporated  
semi hermetic compressor BITZER  
Elimination vibration and silent aspiration back  
Pressure HP security and BP adjustable  
soundproofing sound simple or enhanced Low  
condenser fan speed 6P  
condenser fan speed variator  
security nitrogen load.