

GCM502PD01F

MULTI-COMPRESSORS POWER PLANT DRIVEN WITH CONDENSERS

The central multicompresseurs Zanotti, thanks to the installation of many solutions we have developed, and use of high reliability components were designed and produced to meet the specific requirements of each client in the refrigeration sector.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -5°C	32542 W
T° Evaporation -10°C	26961 W
T°Evaporation -15°C	21652 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -5°C	-
T° Evaporation -10°C	24214 W
T°Evaporation -15°C	19262 W

Technical Data

Voltage	400V/3N~/50 HZ
----------------	----------------

STANDARD FEATURES:

Compressors:

Rotary in suction and
Resistance
Seeing crankcase oil
Interior protection against overheating engine surge and
Fixing rubber shock absorbers

regulation oil

oil separator
Collector equalizer
oil reservoir oil Régulateur
mechanical level
(Equalization between semi-hermetic compressors.

Chassis:

bent sheet metal bolted and galvanized steel and painted
with epoxy powder

Aspiration:

Filter cartridge valves taking pressure valves
intervention
Refoulement
valves taking pressure valves
intervention

Security
Pressure



high and low pressure
Protection Domestic compressors
Thermal Protection