ZANOTTI FRANCE
306 boulevard Charles de Gaulle, 92390 Villeneuve la Garenne, FRANCE
tel: +33 (0)1 41 21 83 00 fax: +33 (0)1 41 21 83 09
www.zanottifrance.com

GCU4060T01F CENTRAL PACKAGE LOW NOISE LEVEL

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -5°C	11289 W
T° Evaporation -10°C	9768 W
T°Evaporation -15°C	8340 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -5°C	10367 W
T° Evaporation -10°C	8966 W
T°Evaporation -15°C	7664 W

Technical Data

Voltage	400V/3N~/50 HZ
Power nominal absorption	5.06 kW/10.44 A
Mass	147 KG
Air Volume Condenser	7800 M3/H
Connections refrigerated aspiration	1"1/8
Connections liquid aspiration	1/2"
DB(A)	33
Body size	4

STANDARD FEATURES:

Mini driven power plant
Incorporated electric cupboard
2 COPELAND compressor scrolls and available in digital version (reduced power 10 to 100%)
Pressure HP security and BP adjustable
Tank with liquid safety valve and fluid line
Soundproofing voice strengthened double skin
Low speed ventilation condenser
Automate regulatory management
load safety compressor nitrogen.

The continuous improvement of our products can cause some variations in this document even without notice.

© ZANOTTI FRANCE