

GCU5120T01F/D

CENTRAL PACKAGE LOW NOISE LEVEL,

available in standard or digital version with compressors 1xZB45 + 1xZBD45

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -5°C	24514 W
T° Evaporation -10°C	20970 W
T°Evaporation -15°C	17744 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -5°C	22300 W
T° Evaporation -10°C	19081 W
T°Evaporation -15°C	16130 W

Technical Data

Voltage	400V/3N~/50 HZ
Power nominal absorption	9.71 kW/20.08 A
Mass	349 KG
Air Volume Condenser	15600 M3/H
Connections refrigerated aspiration	1"3/8
Connections liquid aspiration	5/8"
DB(A)	37
Body size	5



STANDARD FEATURES:

Mini driven power plant
Incorporated electric cupboard
2 COPELAND compressor scrolls and available in digital version (reduced power 10 to 100%)
Pressure HP security and BP adjustable
Tank with liquid safety valve and fluid line
Soundproofing voice strengthened double skin
Low speed ventilation condenser
Automate regulatory management
load safety compressor nitrogen.