

HCU4100T01F

CENTRAL PACKAGE LOW NOISE LEVEL

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -25°C	9025 W
T° Evaporation -30°C	7564 W
T° Evaporation -35°C	6241 W
T° Evaporation -40°C	5027 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -25°C	8244 W
T° Evaporation -30°C	6917 W
T° Evaporation -35°C	5743 W
T° Evaporation -40°C	4625 W

Technical Data

Voltage	400V/3N~/50 HZ
Power nominal absorption	6.34 kW/12.9 A
Mass	171 KG
Air Volume Condenser	7600 M3/H
Connections refrigerated aspiration	1"3/8
Connections liquid aspiration	1/2"
DB(A)	35
Body size	4



STANDARD FEATURES:

Mini driven power plant
 Incorporated electric cupboard
 2 COPELAND compressor scrolls and available in digital version (reduced power 10 to 100%)
 Pressure HP security and BP adjustable
 Tank with liquid safety valve and fluid line
 Soundproofing voice strengthened double skin
 Low speed ventilation condenser
 Automate regulatory management
 load safety compressor nitrogen.