

HCU4120T01F

CENTRAL PACKAGE LOW NOISE LEVEL

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -25°C	11627 W
T° Evaporation -30°C	9713 W
T° Evaporation -35°C	7996 W
T° Evaporation -40°C	6483 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -25°C	10639 W
T° Evaporation -30°C	8908 W
T° Evaporation -35°C	7334 W
T° Evaporation -40°C	5934 W

Technical Data

Voltage	400V/3N~/50 HZ
Power nominal absorption	8.24 kW/16.56 A
Mass	175 KG
Air Volume Condenser	7300 M3/H
Connections refrigerated aspiration	1"3/8
Connections liquid aspiration	1/2"
DB(A)	39
Body size	4



STANDARD FEATURES:

Mini driven power plant
Incorporated electric cupboard
2 COPELAND compressor scrolls and available in digital version (reduced power 10 to 100%)
Pressure HP security and BP adjustable
Tank with liquid safety valve and fluid line
Soundproofing voice strengthened double skin
Low speed ventilation condenser
Automate regulatory management
load safety compressor nitrogen.