

HCU4150T01F

CENTRAL PACKAGE LOW NOISE LEVEL

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -25°C	13482 W
T° Evaporation -30°C	11390 W
T° Evaporation -35°C	9347 W
T° Evaporation -40°C	7416 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -25°C	12278 W
T° Evaporation -30°C	10391 W
T° Evaporation -35°C	8491 W
T° Evaporation -40°C	6685 W

Technical Data

Voltage	400V/3N~/50 HZ
Power nominal absorption	11.31 kW/22.46 A
Mass	287 KG
Air Volume Condenser	7300 M3/H
Connections refrigerated aspiration	1"5/8
Connections liquid aspiration	5/8"
DB(A)	43
Body size	4



STANDARD FEATURES:

Mini driven power plant
Incorporated electric cupboard
2 COPELAND compressor scrolls and available in digital version (reduced power 10 to 100%)
Pressure HP security and BP adjustable
Tank with liquid safety valve and fluid line
Soundproofing voice strengthened double skin
Low speed ventilation condenser
Automate regulatory management
load safety compressor nitrogen.