

HCU5200T01F

CENTRAL PACKAGE LOW NOISE LEVEL

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -25°C	20324 W
T° Evaporation -30°C	17018 W
T° Evaporation -35°C	13627 W
T° Evaporation -40°C	9823 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -25°C	18468 W
T° Evaporation -30°C	15616 W
T° Evaporation -35°C	12741 W
T° Evaporation -40°C	9353 W

Technical Data

Voltage	400V/3N~/50 HZ
Power nominal absorption	14.96 kW/30.20 A
Mass	461 KG
Air Volume Condenser	15600 M3/H
Connections refrigerated aspiration	2"1/8
Connections liquid aspiration	5/8"
DB(A)	44
Body size	5



STANDARD FEATURES:

Mini driven power plant
Incorporated electric cupboard
2 COPELAND compressor scrolls and available in digital version (reduced power 10 to 100%)
Pressure HP security and BP adjustable
Tank with liquid safety valve and fluid line
Soundproofing voice strengthened double skin
Low speed ventilation condenser
Automate regulatory management
load safety compressor nitrogen.