

HCU5260T01F

CENTRAL PACKAGE LOW NOISE LEVEL

Condensing unit on the ground or support.

Refrigerating capacity / Coldroom volume T° ext. +35°C

T° Evaporation -25°C	25165 W
T° Evaporation -30°C	21128 W
T° Evaporation -35°C	17346 W
T° Evaporation -40°C	13778 W

Refrigerating capacity / Coldroom volume T° ext. +40°C

T° Evaporation -25°C	22947 W
T° Evaporation -30°C	19291 W
T° Evaporation -35°C	15863 W
T° Evaporation -40°C	12556 W

Technical Data

Voltage	400V/3N~/50 HZ
Power nominal absorption	16.14 kW/32.46 A
Mass	481 KG
Air Volume Condenser	14600 M3/H
Connections refrigerated aspiration	2"1/8
Connections liquid aspiration	5/8"
DB(A)	44
Body size	5



STANDARD FEATURES:

Mini driven power plant
Incorporated electric cupboard
2 COPELAND compressor scrolls and available in digital version (reduced power 10 to 100%)
Pressure HP security and BP adjustable
Tank with liquid safety valve and fluid line
Soundproofing voice strengthened double skin
Low speed ventilation condenser
Automate regulatory management
load safety compressor nitrogen.