

MDB260TR01F

Industrial horizontal Split unit for rooms of means and great volumes.

Autonomous monobloc fitted with body with built-in electrical equipment box for an industrial application of rooms of means and/or great volumes.

Refrigerating capacity / Coldroom volume **T° ext. +35°C**

T°Room +5°C	47834 W / 1319 m ³
T°Room +0°C	42275 W / 1150 m ³
T°Room -5°C	36708 W / 983 m ³

Refrigerating capacity / Coldroom volume **T° ext. +40°C**

T° Room +5°C	44686 W / 1228 m ³
T° Room +0°C	39449 W / 1065 m ³
T° Room -5°C	34229 W / 909 m ³

Technical Data

Voltage	400 V / 3N~/ 50 Hz
Power nominal absorption	24.7 kW
Intensity nominal absorption	54.3 AMP
Mass	872 KG + 480 KG
Air Volume Condenser	22300 m ³
Air volume évaporateur	20500 m ³
Air throw	39 m
Defrost Heater	16440 W

Group fitted with body envisaged for installation with external with built-in electrical equipment box,
Semi hermetic compressor 25 cv equipped with integral protection,
Cast solid evaporator on feet industrialist with blowing by tubes,
Relaxation of gas by thermostatic pressure reducer,
Ventilators high-output helicoid condensers and low noise level,
De-icing cyclic electric automatic completion,
Control of the pressure of condensation,
Winnow solenoid of line,
Indicator of liquid, tank of liquid with preload R404A,
Electromechanical thermostat of regulation integrated in the electrical equipment box.

OPTIONS:

Electronic Variator speed of the rotors condenser,
Condensation with water,
Panel of control separate (for one or more machines assembled in the same room), Relay of control of the supply voltage.

