

MGS32002F

Unit of vertical condensation, split with wall.

Vertical unit split for positive rooms the small ones and average volumes.

Refrigerating capacity / Coldroom volume **T°ext. +35°C**

T° room +5 °C	4149 W / 43 m ³
T° room 0°C	3652 W / 36 m ³
T° room -5 °C	3110 W / 29 m ³

Refrigerating capacity / Coldroom volume **T°ext. +40°C**

T° room +5 °C	3843 W / 39 m ³
T° room 0°C	3381 W / 33 m ³
T° room -5 °C	2865 W / 26 m ³

Technical Data

Power nominal absorption	2.4 kW
Voltage	400 V / 3N~/ 50 Hz
Intensity nominal absorption	6.3 AMP
Mass	79 KG + 28 KG
Air volume condenser	1500 m ³ /h
Air volume évaporator	1800 m ³ /h
Air throw	4 m
Defrost Heather	1400 W

Split with wall fitted with body with integrated electrical equipment box,

Evaporator ceiling light,

Electric de-icing,

Panel of remote regulation,

Compressing hermetic 2 cv equipped with integral protection,

Expansion of gas by capillary,

Fluid R404A,

Sonde of safety for indication alarms clogged condenser,

Piping preloaded into 2,5 m,

Batteries of heat exchange evaporator and condenser by grooved copper tube and aluminium wings,

Câble line, micro cable carry, cable light ceiling light and lamp,

and for the models low temperature, cables for resistance carries (L=2,5 m).

OPTIONS:

Connexion to system of supervision (Télévis),

Condensation with water,

Different voltage.

