



306 boulevard Charles de Gaulle, 92390 Villeneuve la Garenne, FRANCE tel: +33 (0)1 41 21 83 00 fax: +33 (0)1 41 21 83 09 www.zanottifrance.com

BDB860BR01F

Industrial horizontal Split unit for rooms of means and great volumes.

Autonomous monobloc fitted with body with built-in electrical equipment box for an industrial application of rooms of means and/or great volumes.

Refrigerating capacity / Coldroom volume T° ext. +35°C


59610 W / 2303 m ³
51629 W / 1944 m³
44723 W / 1638 m³



T° Room -15°C	54789 W / 2086 m³
T° Room -20°C	47317 W / 1752 m³
T° Room -25°C	40969 W / 1476 m³

Technical Data

Power nominal absorption 47.4 kW Intensity nominal absorption Mass 1350 KG + 670 KG Air Volume Condenser 33300 m³ Air volume evaporateur 32800 m³ Air throw 41 m	rechnical Data	
Intensity nominal absorption Mass 1350 KG + 670 KG Air Volume Condenser 33300 m³ Air volume evaporateur 32800 m³ Air throw 41 m	Voltage	400 V /3N~/ 50 Hz
absorption Mass 1350 KG + 670 KG Air Volume Condenser 33300 m³ Air volume evaporateur 32800 m³ Air throw 41 m	Power nominal absorption	47.4 kW
Air Volume Condenser 33300 m³ Air volume evaporateur 32800 m³ Air throw 41 m	Intensity nominal absorption	108.6 AMP
Air volume evaporateur 32800 m³ Air throw 41 m	Mass	1350 KG + 670 KG
Air throw 41 m	Air Volume Condenser	33300 m³
	Air volume evaporateur	32800 m³
Defrost Heather 32100 W	Air throw	41 m
	Defrost Heather	32100 W



Semi hermetic Compressor 60 cv equipped with integral protection,

Cast solid evaporator on feet industrialist with blowing by tubes,

Relaxation of gas by thermostatic pressure reducer,

Ventilators high-output helicoid condensers and low noise level,

De-icing cyclic electric automatic completion,

Control of the pressure of condensation,

Winnow solenoid of line,

Indicator of liquid, tank of liquid with preload R404A,

Electromechanical thermostat of regulation integrated in the electrical equipment box.

OPTIONS:

Electronic Variator speed of the rotors condenser,

Condensation with water,

Panel of control separate (for one or more machines assembled in the same room), Relay of control of the supply voltage.



