

BSP221TO02F

Split with wall, unit of horizontal condensation.

Horizontal unit split for negative rooms the small ones and average volumes.

Refrigerating capacity / Coldroom volume **T°ext. +35°C**

T° Evaporation -15 °C	2070 W / 16 m ³
T° room -20°C	1681 W / 12 m ³
T° room -25 °C	1298 W / 7.6 m ³

Refrigerating capacity / Coldroom volume **T°ext. +40°C**

T° room -15 °C	1976 W / 14 m ³
T° room -20°C	1596 W / 11 m ³
T° room -25 °C	1218 W / 6.9 m ³

Technical Data

Power nominal absorption	2.1 kW
Voltage	400 V / 3N~/ 50 Hz
Intensity nominal absorption	5.7 AMP
Mass	69 KG + 19 KG
Air volume condenser	1400 m ³ /h
Air volume évaporator	1200 m ³ /h
Air throw	4 m
Defrost Heather	800 W

Split with wall fitted with body with integrated electrical equipment box,

Evaporator compact ceiling light,

Electric de-icing,

Panel of remote regulation,

Compressing hermetic 2 cv equipped with integral protection,

Expansion of gas by capillary,

Fluid R404A,

Sonde of safety for indication alarms clogged condenser,

Piping preloaded into 2,5 m,

Batteries of heat exchange evaporator and condenser by grooved copper tube and aluminium wings,

Câble line, micro cable carry, cable light ceiling light and lamp,

and for the models low temperature, cables for resistance carries (L=2,5 m).

OPTIONS:

Connexion to system of supervision (Télévis),

Condensation with water,

Different voltage.

