

## **RCV201002F**

## **Monobloc with wall for cellar with wine.**

Autonomous monobloc for cellar with wine, plug assembly on the wall with the unit of condensation outside, and the unit of evaporation inside.

### **Technical Data**

<b>Voltage</b>	230 V / 1~/ 50 Hz
<b>Mass</b>	77 KG
<b>Volume</b>	60 m <sup>3</sup> *
<b>Power cold</b>	1400 W
<b>Power hot</b>	1400 W
<b>DB(A)</b>	40

### **Refrigerating capacity / Coldroom volume**

<b>T° ext. +30°C</b>	
<b>T° room +10 °C</b>	1400 W / 60 m <sup>3</sup>



Monobloc with wall fitted with body with integrated electrical equipment box, cast solid

Evaporator, panel of regulation integrated

Compressing hermetic 1/2 cv equipped with integrale protection

Expansion of gas by capillaire

Fluid R404A

Automatic De-icing by air

Operating temperature: the unit of refrigeration functions with T° of adjustable cellar between max +15°C and +5°C mini.

Function cold + heating + control of moisture

Electric cable of raccordement Reduction of the noise by sound-proofing of the compressor

Automatic elimination of the water of condensate without need for connection towards an evacuation

Panel of regulation in frontage allowing the control of the temperature and the hygroscoy

Box of electronic, new order standard, with more facility to use the keyboard to regulate the temperature (phases of cooling and heating) and moisture (humidification and déshumidification). OPTIONS: Complete unit with additional option

"HUMIDIFICATION". \* volume given as an indication for T°int +14°C and T° ext. +30°C with insulated room.