

MGM11002F

Monobloc with wall (with horse or plug)

Autonomous monobloc for positives rooms the small ones and average volumes.

Refrigerating capacity / Coldroom volume **T°ext. +35°C**

T° room +5 °C	1606 W / 12 m ³
T° room 0°C	1431 W / 10 m ³
T° room -5 °C	1236 W / 8.3 m ³

Refrigerating capacity / Coldroom volume **T°ext. +40°C**

T° room +5 °C	1514 W / 11 m ³
T° room 0°C	1352 W / 9.4 m ³
T° room -5 °C	1165 W / 7.6 m ³

Technical Data

Power nominal absorption	0.9 kW
Voltage	230 V / 1~/ 50 Hz
Intensity nominal absorption	5.4 AMP
Mass	64 KG
Air volume condenser	600 m ³ /h
Air volume évaporator	600 m ³ /h
Air throw	4 m

Monobloc with wall fitted with body with integrated electrical equipment box, cast solid

Evaporator, panel of regulation integrated

Compressing hermetic 1 cv equipped with integral protection

Expansion of gas by capillaire

Fluid R404A

Cyclic de-icing by hot gas

Automatic elimination of condensed water

Cable line, micro cable carries, cable light ceiling light and lampe and for the models low temperature, cables for resistance carries (L=2,5 m).

OPTIONS:

Plug for transformation of an application "to horse" with an assembly on wall

Condensation with water

Different voltage

Insonorisation compressor

